

GM-H40L2G LCD 40" Monitor, W-XGA

Highly reliable 40" Professional LCD Display Monitor.



[Description](#)

[Main features](#)

[Additional features](#)

[Technical specs](#)

[Accessories](#)

[Brochures and manuals](#)

[See all in one page](#)



Description

Highly reliable 40" Professional LCD Display Monitor, which gives excellent performance. Its slim design, with side venting, allows for flexible mounting possibilities, including space-saving flush mounting.

Main features

- Wide range of inputs and control connectors ensures systems can be created with ease
- Slim design with side-vent cooling for flush mounting
- Easily replaceable bezel for applying custom colours
- No screen burn-in
- Self-diagnostic indicator lights
- High-speed input switching
- Digital zoom function
- Eco sensor available for self-adjusting brightness level
- Pro version picture-in-picture and picture-by-picture displays

Additional features

- Power-on delay function (reduces the load on the studio's main power supply when multiple units are powered up simultaneously)
- Variety of external control terminals
- Anti-theft security lock
- VESA FDMI standard compliant fixture points

Technical specs

Alignment

Landscape / Portrait

Screen Size:

40"

Format:

16:9

Resolution:

1,366 x 768 pixel

Display Colours:

16.7 million colours (8 bit)

Viewing Angle:

170° typical

Contrast Ratio:

1.000 .1

Brightness:

400 cd/m² max

Video Standards

PAL/SECAM/NTSC,

PAL60, NTSC 4.43, PLA-M, PAL-N

Tuner

w/o

Input connectors:

PC:/Video: VGA to UXGA

DVI: VGA to UXGA (no HDCP)

CVBS, analogue RGB (optional)

Loop-through option

n/a

Video inputs:

1x Y/C or CVBS

1x RGB/HV or 1X YUV

1x DVI
(more inputs through optional boards)

Audio input:
PC: 3.5mm jack
AV: chinch

Audio output:
chinch

Speakers:
3.4W + 3.4W (6 Ohm)

Remote control:
IR: Yes / manual control: Yes

Interface
RS-232C (in)

On screen Menu:
Yes (5) multilingual

Multiscreen
max. 2 x 2

Timer function
Yes

Screen -saver
Yes

Inverse picture function
No

FAN / Cooler
Yes

Mains switch
Yes

Operating Humidity:
20% to 80% (non-condensing)

Mains switch
Yes

Power requirement:
200 /240 VAC

Power consumption:
330 W

Dimensions:
595 x 986 x 123mm (+/-3mm)

Weight:
26.8 kg +/- 10% (W/O stand)

Other:
270108/ds

Accessories

- [IF-CF01CMG](#)
- Component & RGB
- [IF-CF01PNG](#)
- Composite GM-H40
- [IF-CF01RBG](#)
- RGB/Component active-through
- [IF-CF21HDG](#)
- HD/SD SDI emb. Audio
- [TS-CL03SG](#)
- Stand Unit GM-H40L series

- [TS-CV20WG](#)
- Wall Mount, GM-H40L series

Brochures and manuals



[Brochure for GM-H40L2G](#)



[Large HD LCD brochure](#)



[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

Links

Miscellaneous