

VN-V686BU IP PTZ Dome Camera 36x Zoom. Internal

Internal Full Featured PTZ Network Dome Camera with Advanced PTZ Mechanism "Direct Drive Motor"



[Description](#)

[Main features](#)

[Additional features](#)

[Technical specs](#)

[Accessories](#)

[Brochures and manuals](#)

[See all in one page](#)





Description

Internal PTZ Network Dome Camera with Advanced PTZ Mechanism "Direct Drive Motor"

Main features

- Full-frame dual stream
- Progressive Output
- Day / Night function (IR cut filter)
- Easy Wide-D function
- Easy Auto tracking function

Additional features

- 36 x Optical Zoom Lens
- 0.01 deg. Super Accuracy
- Fastest / Slowest Pan Tilt operation
- Silent mechanism
- One-touch Lock Easy installation

Technical specs

Image device:

1/4" Interline transfer scan CCD, 380000 pixels

Minimum required Illumination:

Colour mode: 0.5 lx (video 25%, F1.6, AGC super) 1.0 lx (video 50%, F1.6, AGC super) B&W mode: 0.04 lx (video 25%, F1.6, AGC super) 0.08 lx (video 50%, F1.6, AGC super)

White balance:

ATW (narrow / wide), AWC (one push and manual)

Automatic electronic shutter:

1/60 to 1/10000 (8 steps)

AGC:

OFF/ MID/ HIGH/ SUPER

Sense up

OFF / x2, 4, 8, 16, 32, 64

Back Light Compensation:

On (4 Types) / Off

Day / Night

IR cut filter On / Off

Accessories

- [WB-S681U](#)
- Pendant Mount TK/VN-68X
- [WB-S682U](#)
- Wall Mount TK/VN-68x
- [WB-S685U](#)
- Recess Adaptor TK/VN-68x

Brochures and manuals



[Internal and External IP PTZ Dome Camera Brochure](#)



[VN-V685_686 brochure](#)



[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

Links

Miscellaneous