

## TK-C9200E Camera, 1/3", 580 TVL 12/24V

Fully-fledged surveillance camera with high-resolution images and clear colours in any situation



### [Description](#)

### [Main features](#)

### [Brochures and manuals](#)

### [See all in one page](#)



### **Description**

The TK-C9200E has Auto White Balance which can be applied to a designated area. With this, colour casting can be prevented by setting the white balance within an area while avoiding strong colour zones for best image results.

It also features 3DNR which is the powerful method that improves image quality when footage is taken in the dark. Noise data is detected by comparing some continuous frames and reduced by blending it into other frames over time.

### **Main features**

- High-Resolution of 580 TV Lines
- Super LoLux™ Sensitivity
- Industry-leading S/N Ratio of 52dB

- 3D Noise Reduction
- Up to 128x of Slow Shutter
- Area White Balance
- Black Level Adjustment
- Easy Installation with Well-Conceived Menu
- Variety of Functions for Precise Monitoring
- Automatic Gain Control (AGC)
- Automatic Electronic Shutter (AES)
- 4 Area Patterns for Backlight Compensation (BLC)
- Manual and Auto Tracking White Balance
- 1.4x/2.0x Digital Zoom
- Privacy Mask for protecting against intrusive monitoring
- Display Mode Selection for CRT and LCD
- CCD White Spot Compensation
- Focus Adjustment Mode for accurate focusing
- 24VAC/12VDC Dual Voltage (TK-C9200E) or 220 240VAC (TK-C9201EG) selectable
- Eco-Friendly Super Low Power Consumption - Approx. 40% lower than conventional models

### **Additional features**

### **Technical specs**

### **Accessories**

### **Brochures and manuals**



[\*\*TK-C9200E/TK-C9201EG - English\*\*](#)



[\*\*Prospekt TK-C9200E/-C9201EG\*\*](#)



[\*\*Instruction manual \(from the JVC Professional Europe Service Information System\)\*\*](#)

### **Links**

### **Miscellaneous**