

Model Ref. Suffix (Size)	Broadcast CRT		Performance CRT			Display CRT										
	DT-V1710 CG (17")	DT-V100 CG (10")	TM-H1950 CG (19")	TM-H1750 CG (17")	TM-H150 CG (15")	TM-A210 G (21")	TM-H1900 G (19")	TM-H1700 G (17")	TM-A170 GD (17")	TM-A170 GE (17")	TM-A140 PN (14")	TM-A14 PN (14")	TM-1051 DG (10")	TM-1011 G (10")	TM-A101 GE (10")	
Definition	HD, all types	HD, all types	SD	SD	SD	SD	SD	SD	SD	SD	SD	SD	SD	SD	SD	SD
PAL / NTSC select	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Via menu	Via menu	Auto	Auto
H/Res (TVL)	>800	SD:300, HD:230	750	750	750	450	750	750	750	750	320	320	280	300	300	300
16:9 / 4:3 switchable	✓ & via remote plus 16:9 bezel	✓ & via remote plus 16:9 bezel	✓ & via remote	✓ & via remote bezel option †	✓ & via remote	✓ & via remote	✓ & via remote	✓ & via remote	✓ & via remote bezel option †	✓ & via remote	✓ & via remote	-	-	✓ & via remote	✓ & via remote	✓ & via remote
Input signals:																
HD SDI	see below *	see below **	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SDI	see below *	see below **	see below ***	see below ***	see below ***	-	-	-	SDI x 1	-	-	-	SDI bridged	-	-	-
RGB & component	see below *	-	see below ***	see below ***	see below ***	-	-	-	-	-	-	-	-	-	-	-
Y / C	-	-	4-pin bridged	4-pin bridged	4-pin bridged	4-pin bridged	4-pin bridged	4-pin bridged	4-pin bridged	4-pin bridged	4-pin	4-pin	-	-	-	-
Composite bridged	-	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B	Both A & B
Audio RCA	via IF-C board	via IF-C151HDG	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4	RCA x 4
Functions:																
Under Scan	✓	✓	✓	✓	✓	-	✓	✓	-	-	-	-	✓	✓	-	-
Tally Lamp	Red or green	Red or green	✓	✓	-	-	-	-	-	-	-	-	Red or green	Red or green	-	-
Pulse Cross	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Blue Only	✓	✓	✓	✓	✓	-	-	-	-	-	-	-	✓	✓	-	-
6,500°K / 9,300°K	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	6,500°K only	6,500°K only	✓	✓	6,500°K only	6,500°K only
Area markers	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Colour On / Off	✓	✓	✓	✓	✓	-	-	-	-	-	-	-	✓	✓	-	-
Ext/ Int Sync	✓	Ext only	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Auto Degauss	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rush current delay	✓	-	✓	-	-	-	✓	-	-	-	-	-	-	-	-	-
General:																
Remote Control(s):	(a) RS-485 2 x 9pin D sub	RS-485 2 x RJ45	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	2 x RCA Contact	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x 15pin D sub	-	-	Contact & trigger 1 x RJ-45	Contact & trigger 1 x RJ-45	Contact 2 x RCA
	Contact & trigger 1 x 15pin D sub	Contact & trigger 1 x RJ-45	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Optional Rack Mounting	RK-C1700E £155 8U Single	RK-C101UK £155 5U Double	RK-C1900E £170 9U Single	RK-C1700E £155 8U Single	RK-C150G £100 7U Single	- - -	RK-C1900E £170 9U Single	RK-C1700E £155 8U Single	RK-170UK £135 8U Single	RK-170UK £135 8U Single	RK-A140E £100 7U Single	RK-A14E £100 7U Single	RK-C101UK £155 5U Double	RK-C101UK £155 5U Double	RK-C101UK £155 5U Double	
Power AC	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	120V & 230V	230V	230V	120V & 230V	120V & 230V	120V & 230V	
Power DC	-	-	-	-	-	-	-	-	-	-	-	-	-	12V DC	-	
Consumption Watts	207	140	140	185	185	207	185	160	160	160	126	115	140	140	140	
W x H x D (mm)	395 x 334 x 467	222 x 220 x 319.3	440 x 375 x 496	395 x 334 x 418	360 x 310 x 418	476 x 408 x 492	440 x 375 x 496	395 x 334 x 418	395 x 334 x 418	395 x 334 x 418	346 x 310 x 368.5	368 x 310 x 372	222 x 220 x 360.3	222 x 229 x 338.3	222 x 220 x 316	
Weight (kg)	23.7	7.1	25.6	20.1	16.0	29.0	25.1	19.6	17.0	17.0	12.2	9.5	7.9	7.8	6.8	

* Plug in the optional **HD SDI / SDI**, **SDI only** or **analogue component** cards, (Max total 3) as required, since DT-V1710 has no built-in video or audio connections.

** Screw attach the **IF-C151HDG HD SDI / SDI** screw-on card. No component board, so for analogue, use built-in Video A & B connectors

*** Plug in optional **SDI only** card or **analogue component** card, (Max 1) as required. TM-H monitors have built-in YC and composite connectors.

† Optional 16:9 bezel TB-170UK

HD SDI & SDI Plug-in	
DT-V1710CG only	
IF-C12HSDG	2 x HD In & Out, Embedded audio.
IF-C21HSDG	1 x HD: In & Out, Emb audio, Auto input.
IF-C51HSDG	As IF-C21HSDG, plus Audio bargraphs.
IF-C61HSDG	2 x dual HD SDI / SDI: In & Out, Embedded audio and Audio bargraphs.
HD SDI & SDI Screw-on	
DT-V100CG only	
IF-C151HDG	1 x In & Out, Emb audio, Audio bargraphs.

SDI only Plug-in	
DT-V1710CG, TM-H1950CG, TM-H1750CG and TM-H150CG	
IF-C21SD1GA	2 x SDI In & 1 x Out, Emb audio, Auto input.
IF-C51SD1GA	As IF-C21SDG, plus Audio bargraphs.

Analogue Plug-in	
DT-V1710CG, TM-H1950CG, -H1750CG & -H150CG	
IF-C01COMG	RGB & component